

CW : Car Width
 CD : Car Depth
 HW : Hoist way Width
 HD : Hoist way Depth
 HR : Head Room
 PD : Pit Depth
 M/C : Machine Room Height

Remark :

- Standard Entrance Height 2,100 mm.
- Counter Weight Located at Back Drop.
- Minimum Floor Height 2,500 mm.
- VVVF Inverter Control System.

Speed m/min

Specification	45	60	90	105	120	150
Max. Floor Stop	16	24	28/32*	28/32*	32	32
Max.Travel (m)	40	60	80/105*	80/105*	120	120

*Applicable when rated capacity is 750 kg and over

Elevator				Door		Car Diminsions (mm)			Hoistway (mm)		Head Room (mm)	Pit Depth (mm)
Model	Person	Capacity (kg)	Speed m/min	Door Opening	Clear Opening	CW	CD	CH	HW	HD	HR	PD
P3-CO	6	450	45	800X2100	1000X2200	1400	850	2300	1750	1400	4250	1250
			60								4450	1550
P8-CO	8	550	45	800X2100	1000X2200	1400	1030	2300	1750	1650	4250	1250
			60								4450	1550
			90								4650	1850
			105								4850	2150
P9-CO	9	600	45	800X2100	1000X2200	1400	1030	2300	1750	1700	4250	1250
			60								4450	1550
			90								4650	1850
			105								4850	2150
P10-CO	10	700	45	800X2100	1000X2200	1400	1030	2300	1750	1850	4250	1250
			60								4450	1550
			90								4650	1850
			105								4850	2150
P11-CO	11	750	45	800X2100	1000X2200	1400	1030	2300	1750	1950	4250	1250
			60								4450	1550
			90								4650	1850
			105								4850	2150
			120								5050	2450
			150									
P13-CO	13	900	45	900X2100	1100X2200	1600	1350	2300	2050	2000	4250	1250
			60								4450	1550
			90								4650	1850
			105								4850	2150
			120								5050	2450
			150									
P15-CO	15	1000	45	900X2100	1100X2200	1600	1350	2300	2050	2150	4250	1250
			60								4450	1550
			90								4650	1850
			105								4850	2150
			120								5050	2450
			150									
P17-CO	17	1150	45	1100X2100	1300X2200	2000	1350	2300	2300	2250	4250	1250
			60								4450	1550
			90								4650	1850
			105								4850	2150
			120								5050	2450
			150									